



BA26S SERIES CRYSTAL - 2.1 x 6.2mm – SMD FORMED LEADS

Frequency Range	12.000MHz ~ 27.000MHz
Mode of Oscillation	Fundamental , 3OT
Load Capacitance (CL)	Standard (12.5pF, 6pF) User Spec
Frequency Tolerance (25 °C)	±20 ppm Standard, User Spec
Frequency Stability	±25 ppm Standard, User Spec
Shunt Capacitance (CO)	5.0pF typical
Drive Level (DL)	1.0µW max
Operating/ Storage Temperature Range	-40 °C to +85°C
Aging	±3 ppm per year max

MOTIONAL RESISTANCE (ESR)

Frequency (MHz)	12.000	12.001 < 23.999	24.000 < 27.000
CI (Ω)	120	100	60
Overtone	Fundamental	Fundamental	3 rd Overtone

PART NUMBERING GUIDE



BA26S	Tolerance	Temperature Range/Stability	Load	Freq
	±30ppm = 5	-40 °C to +85°C/ ±50ppm = K	06 = 6pF	27M000
	±50ppm = 6	-40 °C to +85°C/ ±100ppm = L	12.5 = 12.5pF	
			XX = User Spec	

For other Tolerance, Stability, and Temperature options please consult factory

Example P/N: BA26S – 5 – L – 12.5 – 27M000

To Request a Quote click here - www.beckelec.com//request-a-quote/

MECHANICAL DRAWING



The body of the product should be not soldered to the PCB.

6718 N. 59th Avenue, Glendale, AZ 85301 ▪ Phone: 623-435-6555

Website: www.beckelec.com ▪ Email: sales@beckelec.com