



## BC32 SERIES CMOS OSCILLATOR - 3.2 x 2.5 x 1.2mm

Frequency Range	32.768kHz, 0.75MHz to 125.000MHz		
Supply Voltage $\pm 5\%$	1.8V	2.5V	3.3V
Output Load	15pF		
Current Consumption	40mA max		
Temperature Range	-20 °C to +70°C or -40 °C to +85°C		
Operating	-55 °C to +125°C		
Storage	±25 ppm to ±50 ppm		
Frequency Stability	CMOS		
Output	45% to 55%		
Symmetry (Duty Cycle)	10ns max (except 32.768kHz)		
Output Rise / Fall Time (tr/ff)	90% Vdd		
High Output Voltage	10% Vdd		
Low Output Voltage	No Connection		
Pin 1 Tri-state	Output Enable Voltage		
	Output Enable Voltage		
	Output Disable Voltage		
Oscillation Start Up Time	5ms max		
Aging	±3 ppm max		
Phase Jitter (12kHz to 20MHz)	1 ps max		
Period Jitter (Pk to Pk)	±25ps max		
Note 1	Inclusive of calibration, temp stability, supply change, load change, shock and vibration, and 5 years aging		

## PART NUMBERING GUIDE

Series	Voltage	Temperature Range/Stability	Frequency
BC32	1.8V = 1	-20 °C to +70°C /25 ppm = A	25M000
	2.5V = 2	-40 °C to +85°C /25 ppm = B	
	3.3V = 3	-20 °C to +70°C /50 ppm = C	
		-40 °C to +85°C /50 ppm = D	

For other Tolerance, Stability, and Temperature options please consult factory

**Example P/N: BC32 – 3 – B –25M000**

To Request a Quote click here - [www.beckelec.com/request-a-quote/](http://www.beckelec.com/request-a-quote/)

## MECHANICAL DRAWING

